

**Generators** EU5 certified



**EU5 certified**

# Power generator specifications

Our canopied EU5 containers are sound insulated, with super-silent models for extra-sensitive environments. The EU5 line are equipped with built-in AdBlue tank in addition to a built in diesel tank and provides excellent performance .

Ancillaries ensure your power supply meets the highest safety standards, with HV and LV cables, powerlock connectors, fuel tanks and 32- to 3200-A distribution boxes.



## Technical information

Model		XQP115	XQP200	XQP310	XQP550
Frequency	Hz	50   60	50   60	50   60	50   60
Voltage Range	V	400   480	400   480	400   480	400   480
Power Capacity <sup>1</sup>	kVA	115   120	200   225	310   310	550   588
	kW	92   96	160   180	248   248	440   470
Rating	-	Prime	Prime	Prime	Prime
Output <sup>2</sup>	A	166   144	289   271	447   373	794   707
Breaker 4P	A	200	400	630	1250
Fuel tank	L	518	822	667	1125
AdBlue tank	L	28	32	65.6	92
Fuel consumption <sup>2</sup>	L/hr	20.4   21	32.4   39.9	50   56.5	87.4   98.8
AdBlue consumption <sup>3</sup>	L/hr	0.82   0.84	1.3   1.6	2   2.3	3.5   3.95
Running time <sup>3</sup>	hr	25.4   24.7	25   20	13.3   11.8	12.8   11.4
Dimensions [LxWxH]	mm	2970x1150x2076	4085x1420x2350	4085x1514x2277	5420x2040x2434
Weight without fuel <sup>4</sup>	kg	2077	3651	4103	6740
Weight with fuel <sup>4</sup>	kg	2527	4487	4784	7885
Sound level <sup>5</sup>	dBA	64.9	64.6	65.4	70.4
Remote Monitoring	-	Yes	Yes	Yes	Yes

### Details are given for guidance only

1. Performance data quoted in accordance with ISO 8528-1
2. Amps 50HZ at pf 0,8
3. Fuel consumption measured at 75% load. Fuel density is 850 G/L
4. Includes oil and coolant
5. Sound levels given at 75% prime power load 50 Hz at 7m



**We're here  
to help**

