## **Chillers**



## Chiller specifications

Our contained, packaged chiller rental solutions provide chilled liquid for process cooling or temperature control. The units transport cold fluid through flexible hoses to distribution devices. We have an extensive range of air and water cooled chiller hire solutions available for rent.

The units are quiet, easy to operate and equipped with a remote monitoring system. Our chiller hire equipment can easily be combined with air handlers and fan coils for optimum cooling solutions.







All electric

## Chillers

## Technical information

| Model  |                    | EC50                                   | EC100                                    | EC250                                    |
|--|--------------------|--|--|--|
| Cooling capacity <sup>1</sup> (+30 Ambient)  | kW                 | 56                                     | 105                                      | 258                                      |
| Built-in pump  |                    | Yes                                    | Yes                                      | Yes                                      |
| Power supply   | V/Ph/Hz/PE         | 400/3/50/PE                            | 400/3/50/PE                              | 400/3/50/PE                              |
| Power connection   | -                  | CEE 63A (5-pole)                       | CEE 125A (5-pole)                        | M12                                      |
| Power consumption (at +30 ambient, excl. pump)   | kW                 | 17.9                                   | 30.1                                     | 71.5                                     |
| Pump power (Max.)  | kW                 | 3                                      | 5.5                                      | 11                                       |
| EER (excl. pump) <sup>1</sup> (at +30 ambient)   | -                  | 3.13                                   | 3.49                                     | 3.61                                     |
| Power protection (fuse)  | Α                  | 63                                     | 125                                      | 250                                      |
| Hydraulic connections (DIN11851)   | DN [mm]            | 50                                     | 50                                       | 80                                       |
| Max. Starting current  | Α                  | 64                                     | 17                                       | 24                                       |
| Fluid temperature range cooling  | °C                 | -5 / +12                               | -10 / +12                                | -12 / +12                                |
| Dimensions [LxWxH]   | mm                 | 2275x1200x2020                         | 3240x1200x2110                           | 2991x2438x2438                           |
| Full operational weight  | kg                 | 1340                                   | 1895                                     | 3560                                     |
| Forklift pockets   | -                  | Yes                                    | Yes                                      | Yes                                      |
| Max. Sound pressure @ 10 m   | dBA                | 48                                     | 52                                       | 64                                       |
| Recommended Pon Energy Rental genset size  | kVA                | 135                                    | 135                                      | 135                                      |
|  |                    |  |  |  |
| Model  | -                  | EC275                                  | EC550                                    | EC800                                    |
| Cooling capacity <sup>1</sup> (+30 Ambient)  | kW                 | 284                                    | 552                                      | 842                                      |
| Built-in pump  | -                  | Yes                                    | Yes                                      | Yes                                      |
| Power supply   | V/Ph/Hz/PE         | 400/3/50-60/PE                         | 400/3/50-60/PE                           | 400/3/50-60/PE                           |
| Power connection   | -                  | M12                                    | M12                                      | M12                                      |
| Power consumption (at +30 ambient, excl. pump)   | kW                 | 80.3                                   | 155                                      | 230                                      |
| Pump power (Max.)  | kW                 | 3.54                                   | 18.5                                     | 18.5                                     |
| EER (excl. pump) <sup>1</sup> (at +30 ambient)   |                    | 3.70                                   | 3.56                                     | 3.66                                     |
| Power protection (fuse)  | Α                  | 250                                    | 400                                      | 630                                      |
|  |                    |  |  |  |
| Hydraulic connections (DIN11851)   | DN [mm]            | 100                                    | 100                                      | 2x100                                    |
| Hydraulic connections (DIN11851)  Max. Starting current  |                    | 100<br>0                               | 100<br>3                                 | 2x100<br>0                               |
|  | DN [mm]            |  |  |  |
| Max. Starting current  | DN [mm]            | 0                                      | 3  | 0  |
| Max. Starting current Fluid temperature range cooling  | DN [mm]<br>A<br>°C | 0<br>-15 / +15                         | 3<br>-12 / +15                           | 0<br>-12 / +15                           |
| Max. Starting current  Fluid temperature range cooling  Dimensions [LxWxH]                       | DN [mm] A °C mm    | 0<br>-15 / +15<br>2991x2434x2724       | 3<br>-12 / +15<br>6058x2438x2438         | 0<br>-12 / +15<br>7090x2438x2720         |
| Max. Starting current Fluid temperature range cooling Dimensions [LxWxH] Full operational weight | DN [mm] A °C mm    | 0<br>-15/+15<br>2991x2434x2724<br>3650 | 3<br>-12 / +15<br>6058x2438x2438<br>7900 | 0<br>-12 / +15<br>7090x2438x2720<br>9150 |

Details are given for guidance only. Exact equipment may vary according to geographical location and availability.

The majority of our rental solutions is equipped with remote monitoring.

<sup>1.</sup> Cooling capacity based on 12/7°C water temperature |+30°C air ambient